

Report No: L031709007

Issue Date: 3/30/2017

Prepared For: HK Lighting Group
 3529 Old Conejo Road Ste. 118, Newbury Park CA, 91320

Model Number: ZXL-16-A

Test: Photometric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:
IESNA LM79: 2008 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products
ANSI NEMA ANSLG C78.377: 2008 Specification of the Chromaticity of Solid State Lighting Products
ANSI C82.77:2002: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Testing Condition: Fixture is tested with no special conditions.

Sample Arrival Date: 3/22/17

Date of Tests: 3/28/17 - 3/30/17

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S1	11/28/17
ITECH	IT6122	PS-DC03-S1	11/28/17
Fluke Digital Thermometer	52k/J	MT-TP02-GC	11/28/17
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Summary

Manufacturer:	HK Lighting Group
Model Number:	ZXL-16-A
Driver Model Number:	N/A
Total Lumens:	876.50
Input Voltage (VAC/60Hz):	12.00
Input Current (Amp):	1.27
Input Power (W):	9.69
Input Power Factor:	0.63
Current ATHD @ 12V(%):	68%
Current ATHD @ 277V(%):	N/A
Efficacy:	90
Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	0:30
Total Operating Time (Hours):	1:25




FIG.1 LUMINAIRE

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Released by:



Jeff Ahn
Engineering Manager

Test Report Reviewed by:



Steve Kang
Quality Assurance

**Attached are photometric data reports. Total number of pages: 7*



8165 E. Kaiser Blvd. Anaheim, CA 92808
 www.lightlaboratory.com

Photometric Test Report

IES FLOOD REPORT
PHOTOMETRIC FILENAME : L031709007.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] L031709007
 [TESTLAB] LIGHT LABORATORY, INC.
 [ISSUEDATE] 3/30/2017
 [MANUFAC] HK LIGHTING GROUP
 [LUMCAT] ZXL-16-A
 [LUMINAIRE] LED LUMINAIRE, NATA 1451 60
 [BALLASTCAT] N/A
 [OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
 [MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
 [INPUT] 12VAC, 9.69W
 [TEST PROCEDURE] IESNA:LM-79-08

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS

NEMA Type	5 H x 5 V
Maximum Candela	1019
Maximum Candela Angle	-1H -1V
Horizontal Beam Angle (50%)	56.9
Vertical Beam Angle (50%)	56.9
Horizontal Field Angle (10%)	83.0
Vertical Field Angle (10%)	83.0
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	585
Beam Efficiency	N.A.
Field Lumens	830
Field Efficiency	N.A.
Spill Lumens	46
Luminaire Lumens	876
Total Efficiency	N.A.
Total Luminaire Watts	9.69
Ballast Factor	1.00

IES FLOOD REPORT
PHOTOMETRIC FILENAME : L031709007.IES


AXIAL CANDELA

DEG.	HOR.	DEG.	VERT.
90	0	90	0
85	0	85	0
75	4	75	4
65	8	65	8
55	9	55	9
47.5	20	47.5	20
42.5	69	42.5	69
37.5	235	37.5	235
33	366	33	366
29	493	29	493
25.5	600	25.5	600
22.5	691	22.5	691
19.5	780	19.5	780
17	845	17	845
15	890	15	890
13	928	13	928
11	958	11	958
9	982	9	982
7	999	7	999
5	1011	5	1011
3	1018	3	1018
1	1019	1	1019
0	1017	0	1017
-1	1019	-1	1019
-3	1018	-3	1018
-5	1011	-5	1011
-7	999	-7	999
-9	982	-9	982
-11	958	-11	958
-13	928	-13	928
-15	890	-15	890
-17	845	-17	845
-19.5	780	-19.5	780
-22.5	691	-22.5	691
-25.5	600	-25.5	600
-29	493	-29	493
-33	366	-33	366
-37.5	235	-37.5	235
-42.5	69	-42.5	69
-47.5	20	-47.5	20
-55	9	-55	9
-65	8	-65	8
-75	4	-75	4
-85	0	-85	0
-90	0	-90	0

ZONAL LUMEN SUMMARY


Zone	%
0-20	37.4
0-30	68.1
0-40	89
0-60	98.1
0-80	99.8
0-90	100
10-90	91.1
20-40	51.6
20-50	59.6
40-70	10.1
60-80	1.6
70-80	0.7
80-90	0.2
90-110	0
90-120	0
90-130	0
90-150	0
90-180	0
110-180	0
0-180	100

AXIAL CANDELA DISPLAY



Maximum Candela = 1019 Located At Horizontal Angle =-1, Vertical Angle =-1
H - Horizontal Axial Candela
V - Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 1019 Located At Horizontal Angle =-1, Vertical Angle =-1
50% Maximum Candela = 509.5
10% Maximum Candela = 101.9