

ZXL16 Square

(includes former ZXL16-SQ and ZXL16-SQ-NF models)




IP67

ACCENT & LANDSCAPE | ZX16 Series | 2.25"

5 - 10W (500 - 900lm) | 12V | HK LED, RGB, Amber

FEATURES

- Our most versatile square, directional 12V LED modern accent light for most architectural outdoor and landscape lighting environments.
- 5W, 7W, 10W integrated HK LED delivering 500 to 900 lumens. 2200-4000K CCT, including specialty Amber and RGB options.
- Wet Location Listed, IP67 Standard.
- Machined from solid aircraft grade (6061-T6), corrosion-resistant aluminum, then anodized and powder coated to create a highly durable, marine grade finish. Also available in solid brass or stainless steel.
- 90° vertical and 360° horizontal adjustment via locking swivel stem design.
- Modular components, field changeable LED optical beams, and lenses.
- Available with adjustable Angled, Long, and Short Glare Shields and ground, surface, and canopy mounting options.
- Every fixture tested end of line for water tightness and light quality.
- Ships complete with selected accessories installed.



Standard Low Voltage Square Accent: ZXL16-0S1SA-ABR



Finned Low Voltage Square Accent: ZXL16-0S1FA-AAC

SPECIFICATIONS

Materials

Machined from billet 6061-T6 corrosion resistant aluminum with 304 stainless steel hardware. Available in 304/316 stainless steel or 360 brass upon request.

Finish

Aluminum materials are first anodized and then powder coated for a robust, marine grade finish. Stainless steel and brass models are provided with brushed surface.

Hood and Glare Shield

Weeping Hood Style with Angled, Short, or Long Glare Shields. (See page 4 for details).

Voltage

12V AC/DC. Requires remote step down transformer.

Wattage

5, 7, or 10W HK LED delivering 500 to 900 lumens.

Light Engine

Innovative HK LED Light module operates like a lamp and can be easily changed in the field. CRI 90 Standard. Available in CRI 80 or CRI 95 upon request. Standard CCT options are 2700K, 3000K, 3500K, 4000K. Specialty 2200K, 2400K, 2500K, Amber, and RGB options available. Consult factory for specialty LED specification details.

Dimming

MLV or ELV Phase Control dimming.

Optics

Narrow (20°), Medium (33°), Wide (44°) beam spread options available. Accepts up to 3 optical accessories (hexcel louver, optical lenses, dichroic color filters, etc.) Secured place with metal snap ring.

Mounting

Mounts using 1/2"-14 NPS male fitting compatible with all HK Lighting Group mounting devices. (See page 4 for details).

Listings

ETL Listed for Wet Location, IP67 Standard. RoHS Compliant.

ORDERING GUIDE

EXAMPLE: ZXL16-0S1SA-ABL-012V05W-22N-GSA-LVR-MHCS-06

MODEL	OPTIONS				MATERIAL / FINISH				POWER			LIGHT				
ZXL16	OS1				A				012V							
ZXL16 Series 2.25" Accent Light Integrated HK LED	TYPE		STYLE		HOOD		ABL	Aluminum Black	VOLTAGE		WATTAGE		CCT		OPTICS	
	OS1	Low Voltage, Square Accent	S	Standard	A	A: Weeping	ABR	Aluminum Bronze	012V	12V AC	05W	5 Watts (500lm)	22	2200K	N	Narrow (20°)
			F	Finned			AWH	Aluminum White			07W	7 Watts (700lm)	24	2400K	M	Medium (33°)
							AAC	Aluminum Anodized Clear ¹			10W	10 Watts (900lm)	25	2500K	W	Wide (44°)
							NBR	Natural Brass ¹			SPW	Specialty ²	27	2700K	E	Extra Wide (57°)
							NCU	Natural Copper ¹					30	3000K	CC	Custom Optic
							NSS	Natural Stainless Steel ¹					35	3500K		
							CCC	Custom Finish ¹					40	4000K		
													AM	Amber ²		
													RG	RGB ²		

¹ Consult factory for specialty finish quoting and lead times

² For Specialty AM (Amber LED) and RG (RGB LED), select SPW (Specialty) for Wattage. Consult factory for LED technical details before Specification or Order.

OPTIONAL INSTALLED ACCESSORIES

GLARE SHIELD

GSA	A Hood Glare Shield Angled
GSL	A Hood Glare Shield Long
GSS	A Hood Shield Short

OPTIC

LVR	Hexcel Louver
OSL	Overall Spread Lens
LSL	Linear Spread Lens
SOL	Solite Soft Focus
DCF	Dichroic Filter

MOUNTING (Most common listed, see Page 4 for additional options)

GROUND MOUNT	
MHCS-06	6" PVC Single Prong Spike (12V)
MHCS-12	12" PVC Single Prong Spike (12V)
MH02-06-BRZ	6" Stainless Steel 3-Prong Spike (12V) Bronze
MH02-12-BRZ	12" Stainless Steel 3-Prong Spike (12V) Bronze
JB-1	Brass In-ground Junction Box
CANOPY MOUNT	
CM1-XXX	3.75" Square Canopy Plate
CM3-XXX	4.75" Square Canopy Plate
CM5-XXX	5" Round Canopy Plate
CM5-2-XXX	5" Round Canopy Plate - Double
SURFACE MOUNT	
CMLJ-XXX	2.7" Round Surface Box
CB4.0-XXX	4" Round Surface Box
CB5.5-XXX	5.5" Round Surface Box
TREE MOUNT	
TM125-ABR	Aluminum Tree Mount Box (12V)
TM125-TS-ABR	Stainless Steel Strap for TM125
EXTENSIONS	
EX-12-XXX	12" Extension
EX-24-XXX	24" Extension
EL-XXX	Elbow Extension

ADDITIONAL ACCESSORIES (Not installed at time of order)

GLARE SHIELD ACCESSORIES

GSL-SQ-16-XXX	A Hood Glare Shield Long
GSA-SQ-16-XXX	A Hood Glare Shield Angled
GSS-16-SQ-XXX	A Hood Glare Shield Short

OPTIC ACCESSORIES

LVR-16	Hexcel Louver
OSL-16	Overall Spread Lens
LSL-16	Linear Spread Lens
SOL-16	Solite Soft Focus
DCF-16	Dichroic Filter
OPK-16	Optic Kit - Narrow, Medium, Wide

• Consult Accessory Spec Sheet for desired option code.
• XXX represents color option.


OUTDOOR MAGNETIC TRANSFORMERS (120V input/12VAC Output)

TRANSFORMERS (Go to [Accessories](#) for detailed specification)




EXAMPLE: TXM-300-OTR-SS

MODEL		WATTAGE (VA)						PRIMARY VOLTAGE (VAC)	
TXM	Stainless steel, wet location outdoor magnetic transformer Multitap 12-15VAC Output MLV Dimming	150	300					OTR-SS (120V Only)	
TXS	Stainless steel, wet location outdoor magnetic transformer Multitap 12VAC Output MLV Dimming	150	300	600				SS (120V Only)	
TXM	Compact, damp location magnetic transformer 12VAC Output MLV Dimming	20	40	60	100	150	300	120	277
IGT	In ground outdoor magnetic transformer 12VAC Output MLV Dimming	50 (120V Only)			100	300	600	120	277
TXE	In-fixture or near mounted electronic transformer 12VAC Output ELV Dimming Enclosure by others	60						120	277

PRODUCT DRAWINGS




ZXL16-0S1FA
Finned



OPTIONS & ACCESSORIES

OPTIONAL GLARE SHIELD

For use with Square Hood,
fastened with Set Screw




GSA
(angle)

GSL
(long)

GSS
(short)

MOUNTING ACCESSORIES

Canopy Mount:



Fixture On CM3

CM2


CM1

CM3

CM5

CM5-2

Surface Mount Box:



Fixture On CB5.1

CMLJ

CB3.5

CB4.0

CB4.0-SQ

CB5.1

CB5.1-2


CB5.5

CB5.5-2

CB5.5-K/O

CB5.5-K/O-2

Ground Mount:



Fixture On MH02

MHCS

MH02-06

MH02-T-06

MH05

MH02-12

MH02-T-12


MHVL6-12

MHVL12-24

MH01

JB-1

Tree Mount:



Fixture On TM120-TS

TM125

TM125-TS

TM125-TS-2

TM120-TS


TM125-HB

TM120-C-SM-HB

TMR2

TS-SO

Extension:



Fixture With EX,EL


EX

EL

ET

Sign Light Arm: Please reference the Sign & Pole Mounting section in [Accessories](#) on our website.

Notes:




PHOTOMETRY & ENERGY DATA

ZXL16 Square (Narrow)

Input Power	9.5W
Color Temperature (CCT)	3000K
Color Rendering Index (Ra)	83
Beam Angle	20.5°
Max. Candlepower	3507cd
Delivered Lumens	864lm
Efficacy	91lm/W

Polar Graph - Intensity



Cone of Light - Illuminance


Center Beam (fc)	Beam Diameter	Distance
877	0.7'	2.0'
219	1.4'	4.0'
97	2.2'	6.0'
55	2.9'	8.0'
35	3.6'	10.0'

1/2 Beam Angle: 20.5°

ZXL16 Square (Medium)

Input Power	9.5W
Color Temperature (CCT)	3000K
Color Rendering Index (Ra)	83
Beam Angle	32.5°
Max. Candlepower	1842cd
Delivered Lumens	863lm
Efficacy	91lm/W

Polar Graph - Intensity



Cone of Light - Illuminance


Center Beam (fc)	Beam Diameter	Distance
460	1.2'	2.0'
115	2.3'	4.0'
51	3.5'	6.0'
29	4.6'	8.0'
18	5.8'	10.0'

1/2 Beam Angle: 32.5°

ZXL16 Square (Wide)

Input Power	9.5W
Color Temperature (CCT)	3000K
Color Rendering Index (Ra)	83
Beam Angle	44.1°
Max. Candlepower	1332cd
Delivered Lumens	850lm
Efficacy	89lm/W

Polar Graph - Intensity



Cone of Light - Illuminance


Center Beam (fc)	Beam Diameter	Distance
333	1.6'	2.0'
83	3.2'	4.0'
37	4.9'	6.0'
21	6.5'	8.0'
13	8.1'	10.0'

1/2 Beam Angle: 44.1°

ZXL16 Square (Extra Wide)

Input Power	9.5W
Color Temperature (CCT)	3000K
Color Rendering Index (Ra)	83
Beam Angle	56.9°
Max. Candlepower	1019cd
Delivered Lumens	876lm
Efficacy	92lm/W

Polar Graph - Intensity



Cone of Light - Illuminance

Center Beam (fc)	Beam Diameter	Distance
255	2.3'	2.0'
64	4.6'	4.0'
28	6.9'	6.0'
16	9.2'	8.0'
10	11.5'	10.0'

1/2 Beam Angle: 56.9°

WATTAGE MULTIPLIER

Wattage	Multiplier
5 Watt	0.53
7 Watt	0.77
10 Watt	1.00

CCT MULTIPLIER

Color Temp.	Multiplier
2700k	0.97
3000k	1.00
4000k	1.05